



### 箱单 Packing List

Part	Piece	Name		L (m)	B (m)	H (m)	Kg*
	1	Jib section 01		5.16	1.26	0.96	832
	5	Jib section 02		4.12	1.12	1.04	445
	1	Jib end		5.89	1.12	1.76	923
	1	Counter jib		2.88	2.34	0.54	1126
	1	Hoist unit + rope		2.21	0.94	2.38	3248
	1	Luffing unit + rope		1.82	1.89	1.02	2904
	1	Tower head		7.44	1.26	0.8	1503
	2	Cradle		5.93	0.24	0.35	321
	1	Turntable + slewing unit		2.22	2.17	1.89	4141
	2	Jib tie bar 01		4.66	0.13	0.08	73
	8	Jib tie bar 02		4.16	0.13	0.08	64
	1	Damp bar		1.65	1.22	0.22	150
	2	Damp tie bar		1.12	0.05	0.08	3.16
	1	Pulley block		0.62	0.6	0.48	297
	1	Hook		1	0.5	1.9	600

Part	Piece	Name		L (m)	B (m)	H (m)	Kg*
	1	Self dismantling device		1.81	1.28	1.18	199
	1	Electric control box 01		1.3	0.475	1.8	400
	1	Electric control box 02		0.65	0.425	1.45	120
	1	Resistance box		0.82	0.62	1.72	200
	2	Self dismantling beam		1.28	0.32	0.35	64
	1	Cross beam		4.4	4.4	1	3582
	2	Bar for dismantling		0.7	0.08	0.08	4
	1	Cabin		1.5	1	1.9	500

(\*)Weight per piece

### 机构性能 Mechanisms

机构特性 Mechanisms specification											kW
起升 Hoisting		55LVF40	m/min	64	48	32	32	24	16	700m	55
			t	3,6	5,8	8,0	7,6	11,8	16,0		
拉臂 Luffing		30FVF20	min	15°~80°			t=3,0			200m	30
回转 Slewing		5RVF	r/min	0,46							5,5
电源 Power Supply				380V 50Hz / 440V 60Hz							
KVA 供电容量 Necessary Electric Power				100 kVA							

\* 数据可能有所调整，以产品说明书为准。

\* Relative parameter might be adjusted. Final parameter is subject to its instruction manual.